




## BATTERY DIMENSIONS



## SPECIFICATION

Nominal Voltage	12 V	
Capacity (20 hrs, 27°C)	200 Ah	
Dimension	Length (±3mm)	510 mm (20.07 inch)
	Width (±3mm)	190 mm (7.48 inch)
	Height (±3mm)	376 mm (14.80 inch)
	Total Height (±3mm)	412 mm (16.22 inch)
Approx Net Weight (±3%)	60.5 Kg (133.38 lbs)	
Approx Gross Weight (±3%)	62.2 Kg (137.13 lbs)	
Design Life	5 ~ 7 Years	

## CHARACTERISTICS

Capacity (@27°C)	20 hrs Rate	200 Ah
	10 hrs Rate	180 Ah
	5 hrs Rate	150 Ah
Nominal Backup @ 400 watt (27°C)		210 min
Ah Efficiency (%)		94.50
Wh Efficiency (%)		82.07
Self Discharge (27°C)	3 Month Storage	Remaining Capacity: 88%
	6 Month Storage	Remaining Capacity: 75%
Operating Temperature Range	Discharge	-15°C ~ 50°C
	Charge	-15°C ~ 50°C
	Storage	-15°C ~ 40°C
OCV at 100% SOC		12.60 - 12.70
Charge Methods (CV Charge 27°C) Cyclic Use	Cycle Use 14.4 to 14.6 volt	
	Max. Current 20A	
	Temp Compensation 15mV/°C	
Charge Methods (CV Charge 27°C) Float Use	Standby Use 13.5 to 13.8 volt	
	Max. Current 20A	
	Temp Compensation 15mV/°C	

## TECHNICAL FEATURES

- 1) Advanced Tubular Technology (ATT)
- 2) Uniform micro hardness of Spine Grid
- 3) Corrosion Resistant
- 4) Long Life
- 5) Highest Reliability and Consistant Backup
- 6) Very Low Self Discharge
- 7) Suitable for deep cyclic applications
- 8) Ultra-low maintenance

## APPLICATIONS



Home UPS/Solar



Telecom Communication Equipments



Fire Alarm & Security Systems



Medical Instruments



Computer Backup



Electronic PABX system




Power plant and substations




Process instrumentation and control


### DISCHARGE CHARACTERISTICS




### SELF DISCHARGE CHARACTERISTICS



### FLOAT CHARGING CHARACTERISTICS



### CYCLE SERVICE LIFE @ 27°C



**OKAYA POWER PVT. LTD.**

D-8, Udyog Nagar, Rohtak Road, New Delhi-41, India.

E-mail: [okayacare@okaya.in](mailto:okayacare@okaya.in) | Web.: [www.okaya.in](http://www.okaya.in)

