


CENTRIFUGAL MONOBLOCK PUMPS



Specification

Power	1 to 2HP
Speed	2900 rpm
Version	1Ph 230V, 50Hz
Duty	S1 (Continuous)
Protection	IP 54
Insulation Class	B
Head Range	6 to 26m
Flow Range	42 to 670 lpm

Material of Construction

Pump Casing	Cast Iron
Motor Body	Aluminium Die Casting
Impeller	Cast Iron / SS / Noryl
Shaft	SS 410
Mech. Seal	Carbon Ceramic

Operating Conditions

Max. Liquid Temp.	upto 60°C
Suction Lift	8m

Applications

Residential
Garden

Performance Table

Model	HP	kW	Pump Size (mm)	Phase	Discharge in LPM	Head in Meter										
						6	9	12	15	18	21	24	27	30	33	
CMA-3/07SN	1	0.75	25 x 25	1Ph			100	88	78	65	42					
MCS-09/11	1.5	1.1	32 x 25	1Ph						169	151	141	120	90	39	
MCC-12/11	1.5	1.1	40 x 40	1Ph			282	260	240	203	168	120				
MCC-24/11	1.5	1.1	50 x 50	1Ph			456	396	312	144						
MCC-25/15	2	1.5	65 x 50	1Ph			501	399	258							
MCC-30/15	2	1.5	75 x 75	1Ph			660	546	423	156						