




BATTERY DIMENSIONS



SPECIFICATION

Nominal Voltage		12 V
Capacity (20HRS, 27°C)		250 AH
Dimension	Length (±3mm)	510 mm (20.07 inch)
	Width (±3mm)	190 mm (7.48 inch)
	Total Height (±3mm)	412 mm (16.22 inch)
Approx Net Weight (±3%)		71.5 Kg (157.63 lbs)
Design Life		5 ~ 7 Years

CHARACTERISTICS

Capacity (@27°C)	20 HRS Rate	250AH
	10 HRS Rate	212AH
	5 HRS Rate	178AH
Nominal Backup @ 400 watt (27°C)		310min
AH Efficiency (%)		94.5
Wh Efficiency (%)		82.07
Self Discharge (27°C)	3 Month Storage	Remaining Capacity: 88%
	6 Month Storage	Remaining Capacity: 75%
Operating Temperature Range	Discharge	-15°C ~ 50°C
	Charge	-15°C ~ 50°C
	Storage	-15°C ~ 40°C
OCV at 100% SOC		12.60 - 12.70
Charge Methods (CV Charge - 27°C) Cyclic Use	Cycle Use 14.4 to 14.6 volt	
	Max. Current 25A	
	Temp Compensation 15mV/°C	
Charge Methods (CV Charge - 27°C) Float Use	Standby Use 13.5 to 13.8 volt	
	Max. Current 25A	
	Temp Compensation 15mV/°C	

TECHNICAL FEATURES

- 1) HADI TALL Tubular Technology
- 2) Uniform micro hardness of Spine Grid
- 3) Corrosion Resistant
- 4) Long Life
- 5) Highest Reliability and Consistant Backup
- 6) Very Low Self Discharge
- 7) Suitable for deep cyclic applications

APPLICATIONS



Home UPS/ Solar use



Telecom Communication Equipments



Fire Alarm & Security Systems



Medical Instruments



Computer Backup



Electronic PABX system




Power plant and substations




Process instrumentation and control


FLOAT CHARGING CHARACTERISTICS




CYCLE SERVICE LIFE @ 27 °C



DISCHARGE CHARACTERISTICS



SELF DISCHARGE CHARACTERISTICS



OKAYA POWER PVT.LTD.

D-8, Udyog Nagar, Rohtak Road, New Delhi-41, India.
Tel.: 011-45112300, 011-47451500 | Helpline.: 9818909090
E-mail: myemail@okayapowerltd.com

