




BATTERY DIMENSIONS



SPECIFICATION

Nominal Voltage		12 V
Capacity (20HRS, 27°C)		200 AH
Dimension	Length (±3mm)	510 mm (20.07 inch)
	Width (±3mm)	190 mm (7.48 inch)
	Total Height (±3mm)	412 mm (16.22 inch)
Approx Net Weight (±3%)		60.69 Kg (133.79 lbs)
Design Life		5 ~ 7 Years









CHARACTERISTICS

Capacity (@27°C)	20 HRS Rate	200AH
	10 HRS Rate	180AH
	5 HRS Rate	150AH
Nominal Backup @ 400 watt (27°C)		220min
AH Efficiency (%)		94.50
Wh Efficiency (%)		82.07
Self Discharge (27°C)	3 Month Storage	Remaining Capacity: 88%
	6 Month Storage	Remaining Capacity: 75%
Operating Temperature Range	Discharge	-15°C ~ 50°C
	Charge	-15°C ~ 50°C
	Storage	-15°C ~ 40°C
OCV at 100% SOC		12.60 - 12.70
Charge Methods (CV Charge - 27°C) Cyclic Use	Cycle Use 14.4 to 14.6 volt	
	Max. Current 20A	
	Temp Compensation 15mV/°C	
Charge Methods (CV Charge - 27°C) Float Use	Standby Use 13.5 to 13.8 volt	
	Max. Current 20A	
	Temp Compensation 15mV/°C	


TECHNICAL FEATURES

- 1) HADI TALL Tubular Technology
- 2) Uniform micro hardness of Spine Grid
- 3) Corrosion Resistant
- 4) Long Life
- 5) Highest Reliability and Consistant Backup
- 6) Very Low Self Discharge
- 7) Suitable for deep cyclic applications


APPLICATIONS

-  Home UPS/ Solar use
-  Telecom Communication Equipments
-  Fire Alarm & Security Systems
-  Medical Instruments
-  Computer Backup
-  Electronic PABX system
-  Power plant and substations
-  Process instrumentation and control


FLOAT CHARGING CHARACTERISTICS




CYCLE SERVICE LIFE @ 27 °C



DISCHARGE CHARACTERISTICS



SELF DISCHARGE CHARACTERISTICS



OKAYA POWER PVT.LTD.

D-8, Udyog Nagar, Rohtak Road, New Delhi-41, India.
Tel.: 011-45112300, 011-47451500 | Helpline.: 9818909090
E-mail: myemail@okayapowerltd.com

